

## Tender text

### ETS-8060TW/WS

#### PA hi-fi column speaker

- High-quality 2-way column speaker with excellent sound characteristics
- 100 V line technique or 8  $\Omega$  operation
- 4 x 5 cm (2") full range speaker with paper cone
- 25 mm (1") centrally arranged dome tweeter
- 3 power taps: 20/10/5 W
- Power capability: 40 W in 8  $\Omega$  operation
- Connection is made via cable with high-strength cable gland (length: 2 m)
- Robust aluminium cabinet of an appealing design with cloth-covered plastic front protective grille
- Supplied with pivoting and tiltable wall bracket

#### Specifications:

Active/passive	passive
Transmission method	100 V
Power rating (RMS)	20/10/5 W (100 V) 40 W (8 $\Omega$ )
Impedance	8 $\Omega$
Frequency range	160-20,000 Hz
Full range speaker	4 x $\varnothing$ 50 mm
Tweeter	1
Number of speakers	5
Sensitivity	89 dB/W/m
Max. rated SPL	107 dB
Radiation angle, horizontal	180°
Radiation angle, vertical	40°
Housing material	aluminium
Colour	white
Mounting device	wall bracket
Admiss. ambient temp.	0-40 °C
Dimensions	85 x 430 x 70 mm
Width	85 mm
Height	430 mm
Depth	70 mm
Weight	2.5 kg
Inputs	cable

Brand: MONACOR

Type: ETS-8060TW/WS

Quantity: 1

Packing dimensions (W x H x L): 0.17 x 0.15 x 0.51 m

Gross weight: 2.56 kg

Net weight: 2.2 kg

Item weight (w/o accessories): 2.2 kg