

Tender text

INC-2722BCP

PROJECT Line 2 megapixel network colour camera,

with integrated micro SD card recorder, webserver and professional day/night function.

- For identifying number plates, supplied with software for analysing and storing
- Weatherproof outdoor housing
- Motorised zoom lens (7-22 mm)
- Viewing angle: 16.8-40.7°
- Due to 17 super-bright LEDs, suitable for application in the dark, IR operating range: 70 m, with optimum reflection
- Integrated micro SD card recorder (for media up to 64 GB, not supplied)
- Image compression: H.264, MJPEG
- Video motion detector function
- Power is provided via Power over Ethernet (PoE) or via optional power supply
- Supplied with wall bracket

Compatible with PROJECT Line network video recorders NWR-801POE, NWR-1608POE and NWR-3216POE, ONVIF.

Specifications:

| | |
|-----------------------|--|
| Camera | |
| Design | bullet |
| Image sensor | 8.76 mm (1/2.9") CMOS, progressive scan |
| Number of pixels | 1920 x 1080 pixels max. |
| Resolution | 2 MP |
| Lens | 7-22 mm/1:1.6 |
| Viewing angle | 16.8-40.7° |
| Min. illumination | 0.01 lx (colour) 0 lx (B/W) |
| Webserver | integrated |
| Video streaming | mainstream 500-12,000 kbps, substream 100-6,000 kbps |
| Compression method | H.264, MJPEG |
| Protocols | IPv4, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP, IGMP, unicast and multicast |
| Protective class | IP67 |
| Power supply | PoE or DC 12 V/700 mA |
| Operating voltage | DC 12 V |
| Admiss. ambient temp. | -30-+60 °C |
| Dimensions | Ø 110 mm x 377 mm |
| Width | Ø 110 mm |

| | |
|----------------|--------------------------------------|
| Depth | 377 mm |
| Weight | 1.68 kg |
| Other features | 1 x alarm input, 1 x alarm output |
| Ethernet | RJ45, 10/100 Mbps |
| Audio | 1 x RCA (in/out) |
| Video | BNC (test output) |

Brand: MONACOR

Type: INC-2722BCP

Quantity: 1

Packing dimensions (W x H x L):

Gross weight: 2.2 kg

Net weight: 2 kg

Item weight (w/o accessories): 1.68 kg