

Tender text

NBB-75DFGX

NEUTRIK UHD BNC panel jacks provide low return loss values at high frequencies, which typically occur in high-definition video signal transmissions. The machined brass body ensures a rugged and non-abrasive connection. Due to being recessed in the D series body (audio industry standard) they are additionally protected.

UHD BNC feed-through panel jack, 75 Ω , earthed

- Gold-plated cage type contact, optimised for UHD signals like 4 K or 8 K
- High-quality PTFE insulation
- Body with antraloy coating
- BNC insert is earthed via body
- Earthed panel mounting
- D series
- Colour coding possible
- Compatible with customary BNC cable connectors

Specifications:

Description	panel jack
Type	NEUTRIK BNC feed-through
Quantity	1
Features	PTFE insulation, gold-plated contacts
Colour/colour coding	black
Insulating resistance	> 5 G Ω
Dielectric strength	1.5 kV
Connection	2 x BNC, 75 Ω
Material	metal
Admiss. ambient temp.	-30-+85 °C
Weight	29 g
Other features	D series

Brand: NEUTRIK

Type: NBB-75DFGX

Quantity: 1

Packing dimensions (W x H x L):

Gross weight: 0.031 kg

Net weight: 0.029 kg

Item weight (w/o accessories): 0.029 kg