

Tender text

PMX-164

Powered mixer, 70 W, 4 Ω

- Audio mixer and audio amplifier built into a wooden housing with black felt covering
- 5 mono input channels, each with gain control, 2-way tone control and effect control
- 1 mono input channel (stereo input) with gain control, 2-way tone control and effect control
- Integrated Bluetooth receiver
- Integrated MP3 player with USB port, SD card slot and illuminated LCD
- Adjustable digital delay
- Tape record and CD/tape play connections
- 5-band graphic equalizer
- Low-pass filter: 200 Hz, 6 dB/oct.
- Sub-out output for connecting an active subwoofer

Specifications:

No. of channels	6
No. of inputs	13
Mic input	1.5 mV, bal., 6 x 3-pole XLR
Line input	15 mV, 5 x 6.3 mm jack, 1 x RCA L/R, 550 mV, 1 x 6.3 mm jack
Tape (play)	200 mV, 1 x RCA L/R
Monitor output	7.5 V, 1 x 6.3 mm jack (sub out)
Tape (rec)	550 mV, 1 x RCA L/R
Frequency range	20-20,000 Hz
THD	0.1%
S/N ratio	> 65 dBA
Equalizer bass	\pm 15 dB/80 Hz
Equalizer treble	\pm 15 dB/10 kHz
equalizer	\pm 12 dB, 100/500 Hz/1/2.5/10 kHz
Amplifier	Power rating 2 x 40 W/4 Ω , 2 x 30 W/8 Ω Peak music power output 2 x 70 W/4 Ω , 2 x 50 W/8 Ω
Power supply	~ 230 V/50 Hz/210 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	210 VA
Admiss. ambient temp.	0-40 $^{\circ}$ C
Width	400 mm
Height	220 mm
Depth	230 mm
Weight	7 kg

Brand: IMG STAGELINE

Type: PMX-164

Quantity: 1

Packing dimensions (W x H x L): 0.27 x 0.25 x 0.44 m

Gross weight: 7.5 kg

Net weight: 7 kg

Item weight (w/o accessories): 7 kg